



PowerMon
The No.1 Innovation

Silikometer

Advantages

- precise results
- connection of external, physical measuring sensors
- fully automatic operation
- easy, comfortable operation
- fast data transfer
- self-monitoring system
- remote maintenance and network ability
- graphic user interface with interactive Touch Screen operation
- update of the operating software or download of data by USB stick
- minimum operating cost by small reagent consumption
- second measuring point without surcharge
- operation also possible without housing

The PowerMon Silikometer is a versatile applicable on-line measuring instrument. It guarantees a permanent optimal water quality by the continuous supervision of the silica concentration in boiler feed water or during water treatment.

Apart from higher precision and shortening of the measuring cycles the PowerMon offers a special highlight: For the measurement of most diverse parameters (e.g. oxygen, pH, redox, conductivity etc.) the connection of various sensors via interface is possible!

For the individual sensors the PowerMon automatically takes over the functions of a transducer. It is also possible to set the separate results against each other.

A remote supervision enables the permanent control of the correct function of your plant. The highest possible data transfer over the interfaces, as well as the operation of the PowerMon via the touch screen user interface ensures an easy and user friendly operation.

Applications

- power plants
- chip-Industry
- ultrapure water treatment
- supervision of boiler feed water
- and others

PowerMon Silikometer



The compact and modular design of the PowerMon can contain up to six on-line measuring points in one device and enables a space-saving and economic operation



Technical Data

Measuring methods

cyclic, colorimetric

Measuring cycle

min. 10 min / typical 15 min

Measuring range

0-5 to 0-1100 ppb

Further parameters and measuring ranges on request

Precision

3% or 0.1 ppb
(whatever is higher)

Detection limit

100 / 150 ppt

Drift

typ. < 0.2% of measuring range
(end of value)

Reagent supply

typ. 12 weeks
depending on range

Number of measuring points

max. 6

Output signal

0/4-20 mA
max. load 500 OHM
characteristic curve:
linear/logarithmic
galvanically isolated

Interfaces

USB / Ethernet
Option:
modem: analog, GSM, ISDN
Profi Bus DP

Relay contacts

4/12 potential free contacts
free allocable
(e.g. alarm contact)

Digital inputs

4/12 e.g. activating and deactivating
of measuring points, system control

Sample

pressure-free
Temperature
15 - 45°C (288 - 308 K)
Flow
3 - 10 l/h
free from suspended
matter and oil
Connection
tube, flexible
(ID 1.5 - 3 mm)

Drain

pressure-free
tube, flexible
(ID 10 mm)

Power supply

85...264 VAC at
47...63 Hz or
120...370 VDC

Power consumption

max. 150 VA

Environmental temperature

15 - 35°C (288 - 308 K)

Installation

wall-mounted

Protection class (EN 60529)

IP 65 (electronics)
IP 54 (with housing)
IP 21 (with jacket)

Weight

housing with reagent cabinet
53 - 60 kg without reagents

Dimensions (height x width x depth)

housing: 700x600x320 mm
with reagent cabinet:
1100x600x354 mm

* For further informations please
contact our technical Support

Bran+Luebbe GmbH - P.O. Box 1360 - D-22803 Norderstedt
Phone: +49 (0) 40 - 522 02 -0 - Fax: +49 (0) 40 - 522 02 444
E-mail: bl@spx.com - <http://www.branluebbe.com>

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.spxpe.com.

SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

Issued: 7.1.4 - 0.5 - E 10/2008

Copyright © 2007, 2008 SPX Corporation

SPX®

PROCESS EQUIPMENT